USER'S MANUAL

CHANDELIER ITEM# 6737-6H

WARNING

1. Shut off the power to the area where you will be working.
2. Use 60 watt maximum type A bulb.
3. Do not use polish or cleaner on your lamp, just wipe with soft cloth.

STEP 1 -- UNPACK

1. Carefully unpack your new fixture and lay out all the parts on a clear surface.
2. The bag includes a mounting pack.

STEP 2 -- CHANDELIER ASSEMBLY

1. Thread the PIPE(16) to the NIPPLE(29),Put the ARM(30) to the FIXTURE through PIPE(16), then screw the NIPPLE(12) into the PIPE(16),attach the MIDDLE COVER(15) to the ARM(30) through NIPPLE(12), then put the TUBE(14), TOP COVER(13) and BALL(11) onto it, Then screw with the HEX NUT(10) and LOOP(9) until snug.
2. Screw the NIPPLE(19) to the CONNECTOR(17) with HEX NUT(18), Attach the BOTTOM COVER(20) onto the FIXTURE, then thread with the FINIAL(21).
3. Put the CANDLE COVER(23) onto the SOCKET(22), then clip the Shade(24) to the bulb.
4. Adjust the distance of ARMS(31) to be equal.
5. Hang the CRYSTAL(25)—6PCS, CRYSTAL(26)—24PCS,CRYSTAL(27)—13PCS and CRYSTAL(28)—6PCS to the FIXTURE.(Please see the instruction in the diagram).

STEP 3 --- FIX WIRE INSTALLATION

※We advise contacting a qualified electrician for this step.

1. Thread Nipple (3) into Loop (6) until snug.
2. Place lock Washer (2) over end of nipple protruding through crossbar and thread hex nut (1) onto nipple until tight.
3. Thread other end of Nipple (3) with loop attached into Crossbar (4) until snug.
4. Take this crossbar assembly and mount to ceiling junction box with Junction box threads (5), Tighten thread securely with screwdriver.
5. Lace the fixture wires through the chain. Slip loop collar (8) over the chain, Then do the same with Canopy (7).
6. Cut the wire plug off, Feed the fixture wires through the Loop (6),Nipple (3) and pull until taut.
7. Connect fixture wire to the wire from junction box with wire connectors. See paragraph below.
8. Push canopy (7) up against ceiling and secure with loop collar (8).

※ WIRE CONNECTION

FOR WIRE CONNECTION, BE SURE TO CONNECT, FIXTURE SMOOTH WIRE TO THE BLACK HOUSE WIRE, RIBBED WIRE TO THE WHITE HOUSE WIRE AND FIXTURE GROUND WIRE TO SUPPLY GROUND WIRE WITH WIRE CONNECTORS OR THE FIXTURE GROUND WIRE FROM THE FIXTURE TO THE GREEN GROUND SCREW ON THE MOUNTING BRACKET.

※ **Your installation is now complete. Turn power on.**